

GROUT POWER SPONGE

GROUT POWER SPONGE

- continuous band sponging machine
- for sponging off cement grouts
- quickly cleans off grout
- from quarry tiles & pool surrounds
- granite sets & paviers
- leaves uniform & strong joint
- for external pavements & pedestrian areas
- saves up to 70% of grouting time & labour

The machines use a continuous sponge band that is fed through a water bucket and rollers; the excess sludge and water is squeezed out leaving the sponge clean to repeat the cycle

The Schwammfix machines are for cleaning cements and grouts from quarry tiles, external paviers, natural stone and granite sets

The grout is pumped or poured into the joint; the Schwammfix machine is used to pass over the newly grouted area and to sponge off the residue leaving a clean surface and compact joint

The system improves the joint quality, avoiding washing away the cement in the joint

The machines will mechanically do the time consuming "hands and knees" job of removing cementitious and epoxy grout

APPLICATIONS

- cleaning tiles of cement residues
- sponging off grouts
- finishing granite sets

SWM620P Power Sponge 4hp

Weight 62kg

Size WxL 55x97cm

Height 88cm

Sponge width 36cm

Prep rate 150m/hr

Vibration level 2.5m/s

Noise level 76dBA



SWM620



TILE GROUT POWER SPONGE

TILE GROUT & FLOOR POWER CLEANER, petrol motor

Stock no	Description	Power	Weight	Sponge width	£ ex VAT
540620P	SWM620P 14" power sponge	4hp	62kg	36cm	2595.00

SPONGES, continuous band for cleaning off tiles & paviers

Stock no	Description	Sponge width	£ ex VAT
540361	SWM620 14" fine sponge for grout	36cm	79.00

SPONGES, continuous band for cleaning off tiles & paviers

Stock no	Description	Sponge width	£ ex VAT
540364	SWM620 14" coarse sponge for grout	36cm	129.00

GROUT POWER SPONGES

GROUT POWER SPONGE

- for cement & epoxy grouts
- quickly cleans grout from quarry tiles
- granite sets & paviors
- leaves uniform & strong joint
- for external pavements & pedestrian areas
- saves up to 70% of grouting time & labour

The Schwammfix 880P is a heavier duty version of the 620P and is for cleaning cements and grouts from quarry tiles, external paviors, natural stone and granite sets

The machines will mechanically do the time consuming "hands and knees" job of removing cementitious grouts

The machines use a continuous sponge band that is fed through a water bucket and rollers; the excess sludge and water is squeezed out leaving the sponge clean to repeat the cycle

The sponge cleaning method avoids washing away the cement content in the joint and leaves a uniform, compact joint

Finishing rates up to 200m²/hr

APPLICATIONS

- cleaning tiles of cement residues
- sponging off grouts
- finishing granite sets

SWM880P Power Sponge 4hp

Weight 80kg

Size WxL 60x110cm

Height 96cm

Sponge width 36cm

Prep rate 200m/hr

Vibration level 2.5m/s

Noise level 76dBA



TILE GROUT POWER SPONGE

GROUT & FLOOR POWER CLEANER, petrol motor

Stock no	Description	Power	Weight	Sponge width	£ ex VAT
540370P	SWM880P 14" power sponge	4hp	80kg	36cm	3595.00

REPLACEMENT SPONGES

SPONGES, continuous band for cleaning off tiles, sets & paviors

Stock no	Description	Sponge width	£ ex VAT
540375	SWM880 14" sponge for cement	36cm	169.00

GROUTING TROWEL

TILE & GROUT POWER TROWELS

- rubber bladed power trowel
- easy application for large areas
- compacts grout joints
- helps remove excess cements
- works well in conjunction with sponge machine

The 16" rubber bladed power trowel will apply grout into tile and pavior joints

It leaves a well compacted joint and saves application time and effort, taking the tradesman off his hands and knees

The power grouter can be used on cementitious and epoxy grouts

The 110 volt model is fitted with a 32 amp plug and needs to run off a 5kva transformer

APPLICATIONS

- power floating wet grouts
- finishing epoxy, polymer & cement grouts
- use on natural stone & terracotta tiles
- external paviers & slabs
- swimming pool surrounds

PS43-TG FLOOR SURFACER 1.5kw

Speed 154rpm

Weight 50kg

Size WxL 44x59cm

Height 120cm

Disc 430mm

Prep rate 40m/hr

Vibration level 2.5m/s

Noise level 76dBA

Voltage 110v or 230v

Transformer 5kva, 32 amp plug



PS43-TG
tile grouter



317802
grouter head



GROUTER

FLOOR TILE GROUTER, with rubber trowel blades, for placing tile & cement grouts

Stock no	Description	Power	Weight	Speed	£ ex VAT
316014	PS43-TG cement grouter	1.5kw	50kg	154rpm	799.00

REPLACEMENT FLOOR TILE GROUTER, 17" head with rubber trowel blades

Stock no	Description	Size	£ ex VAT
317802	grouter head & blades	430mm	80.00