

MORTAR SCREW SPRAY PUMP

STX525 SCREW SPRAY PUMP 3 PHASE

- hopper feed screw pump
- for spraying & applying
- repair & refurbishment
- grouting & filling

This screw pump is a hopper feed unit designed to spray pumpable repair mortars and heavy grouts. The pump requires a three phase 415 volt electrical supply and has interchangeable rotors and rubber stators to pump and spray apply heavy bodied cements and mortars.

The material is mixed directly over the hopper using the piggyback RMX100 mortar mixer and discharged into the pump hopper and then pumped to the spray gun for application.

The standard motor supplied is 415 volt three phase.

The pump is available with a range of different rotor-stators setups with outputs from 15 to 30 ltr/min.

The full system includes 2.2kw screw pump, 1.5kw piggyback mixer and 2.2kw 110 volt air compressor. A generator is required to power the pump and spray system.

APPLICATIONS

- pipping & applying
- mortars & cements
- grouts & renovation materials
- heavy bodied coatings
- waterproofing & tanking coatings

STX525 Spray pump 2.2kw 415 volt

Machine weight 89kg

Size WxL 66x160cm

Height 70cm

Hopper tank 80 ltr

Pump output 25 ltr/min

Noise level 59dBA

Generator 6kw 3 phase

Compressor required 1.5kw



780012
spray pump



pump & mixer



787101
spray gun

RENDER & MORTAR PUMP

SCREW SPRAY PUMP, three motor, for plaster, pre-bagged render, mortars, cement coatings & grouts

Stock no	Description	Power	Weight	Output	Hose	£ ex VAT
780012	STX525 spray pump, 3½" stator	2.2kw	89kg	25 ltr/min	25mm	2595.00

HEAVY DUTY MORTAR MIXER, rotary paddle, bottom outlet

Stock no	Description	Power	Weight	Capacity	Drum size ø	£ ex VAT
702100	rotary paddle piggy back mixer	1.5kw	80kg	30-90kg	60cm	1395.00

SPRAY LANCE for high build coatings, cement paints & textures

Stock no	Description	Nozzle	Air cap	Air consumption	£ ex VAT
787101	spray gun 10cfm	10mm	spatter	280 ltr/min @ 3 bar	95.00